

Contact Series

SMOKE DETECTOR



Smoke Detection

The Smoke Detector is designed for use in commercial and residential applications and is engineered to virtually eliminate nuisance alarms and deliver outstanding performance wherever reliable smoke detection is required. Up to 12 devices can be connected together and report to one Sensaphone zone. A 85 dBA audible horn and 9V battery backup is included. This smoke detector can be used with all Sensaphone models.

TECH SPECS

Name	Smoke Detector
Operating Temperature	40° to 100°F 4° to 37°C
Alarm Horn Rating	Meets or exceeds 85dBA at 10'
Certifications/Compliance	ANSI/UL 217 Listed, NFPA 72, IBC/IFC/IRC
Dimensions	5.5" x 5.5" x 1.75" 140 x 140 x 45mm
Power	120VAC 60Hz (9V Battery backup included)
Auxiliary Relay	One Form-A and one Form-C relay output (1.0 A @ 30VDC, 0.3 A @ 125VAC)
Tandem Interconnect	12 Max. Up to 125' between each alarm. 1125' max distance from first to last alarm

All specifications subject to change without notice

Product Name

Part Number

Contact Type Smoke Detector for 120VAC w/ Battery Backup FGD-0049-SQ



Family owned and made in the USA since 1985

901 Tryens Road

Phone: 877-373-2700

Aston, PA 19301

Web: sensaphone.com

