

4-20mA
Series

4-20mA Type Differential Pressure Sensor with Duct Mount Kit



Measure static or differential pressure
 Monitor differential pressures in commercial buildings with an attractive pair of duct mount static pickup tubes. Excellent tolerance to overpressure & vibration reduces field failures. High accuracy digital sensor maintains calibration and reduces callbacks. The sensors monitor positive and negative pressure for application versatility and the LCD is ideal for set-up, troubleshooting and measuring.

TECH SPECS

Media Compatibility	Dry air or inert gas
Input Power	2-wire, loop-powered 4 to 20 mA
Mode	Unidirectional or bidirectional, switch selectable
Pressure Ranges	Uni Directional: 0.1/0.25/0.5/1.0/2.5/5/10" W.C. 25 Pa/50 Pa/100 Pa/250 Pa/0.5 kPa/1 kPa/2.5 kPa F.S. switch selectable Bi Directional: ±0.1/0.25/0.5/1.0/2.5/5/10" W.C. 25 Pa/50 Pa/100 Pa/250 Pa/0.5 kPa/1 kPa/2.5 kPa F.S. switch selectable
Dimensions	3.3" x 4.5" x 2.2" 84mm x 114mm x 55mm
Sensor Series	4-20mA Series
Notes	Requires a 24VDC power supply (FGD-0070)

All specifications subject to change without notice

Product Name	Part Number
4-20mA Differential Pressure Sensor	FGD-0302-DUCT
24VDC Power Supply for 4-20mA Sensors	FGD-0070



Family owned and made in the USA since 1985

901 Tryens Road
Aston, PA 19301

Phone: 877-373-2700
Web: sensaphone.com

