

4-20mA
Series

4-20mA Type Differential Pressure Sensor with Wall Mount Kit



Measure static or differential pressure
 Monitor differential pressures in commercial buildings with an attractive pair of wall/ceiling mount static pickup tubes. Excellent tolerance to overpressure & vibration reduces field failures. High accuracy digital sensor maintains calibration and reduces callbacks. The sensors monitor positive and negative pressure for application versatility and the LCD is ideal for set-up, troubleshooting and measuring.

TECH SPECS

Pressure Ranges	Uni Directional: 0.1/0.25/0.5/1.0/2.5/5/10" W.C. 25 Pa/50 Pa/100 Pa/250 Pa/0.5 kPa/1 kPa/2.5 kPa F.S. switch selectable Bi Directional: ±0.1/0.25/0.5/1.0/2.5/5/10" W.C. 25 Pa/50 Pa/100 Pa/250 Pa/0.5 kPa/1 kPa/2.5 kPa F.S. switch selectable
Accuracy	± 0.5
Connection	Brass barb; .24" (6.1mm) od
Operating Voltage	8.5 to 36 DC
Sensor Series	4-20mA Series
Environmental Rating	IP65, NEMA 4
Notes	Requires a 24VDC power supply (FGD-0070)

All specifications subject to change without notice

Product Name	Part Number
4-20mA Differential Pressure Sensor with Wall Mount Kit	FGD-0302-ROOM
24VDC Power Supply for 4-20mA Sensors	FGD-0070



Family owned and made in the USA since 1985

901 Tryens Road
Aston, PA 19301

Phone: 877-373-2700
Web: sensaphone.com

