



WIRELESS TEMPERATURE DISPLAY WITH BUFFERED TEMPERATURE SENSOR



Buffer temperature fluctuations

The Wireless Temperature Display is used exclusively with the Sensaphone WSG30 to provide an at-a-glance reading of the current temperature wherever the display is installed. By placing the included sensor in a bottle filled with glass beads, users will receive a reading that represents the temperature of the contents of inside of the refrigerator rather than the ambient air temperature. The external probe is wired to the display with the included 12' of wire.

TECH SPECS

Name	Temperature Sensor in Glass Bead Vial
Sensor Temperature Range	-20° to 176°F -28° to 80°C
Accuracy	± 1°F ±.56°C
Wireless Range	300' 90m
Connection	WSG Wireless
Housing	Plastic
Dimensions	4.65" x 3.7" x 1.1" 118 x 94 x 28mm
Notes	(2) AA alkaline batteries will power sensor for 3 years

All specifications subject to change without notice

Product Name	Part Number
WSG Temperature Display with Glass Bead Vial	FGD-WSG-LCDGBV
WSG Temperature Display with Glass Bead Vial w/NIST Certification	FGD-WSG-LCDGBVN



Family owned and made in the USA since 1985

901 Tryens Road
Aston, PA 19301

Phone: 877-373-2700
Web: sensaphone.com

